

**P**

↓
Type

**P****M****R****K45R**

↓
Size

K45R
K50R
K63R
K85R

10

↓
Ratio

Z

↓
Hub

**Z****STANDARD**

K45R ⇨ 0.750"
K50R ⇨ 1.000"
K63R ⇨ 1.250"
K85R ⇨ 1.500"

On request
METRIC
Hollow Shaft

K45R ⇨ 18mm
K50R ⇨ 25mm
K63R ⇨ 25mm
K85R ⇨ 35mm

Ø

↓
Output shaft

**Ø****S****W**

↓
Motor size

**M**

Without flange

Z

For Type - R

WITH NEMA
MOTOR FLANGE

W

⇨ 56C

X

⇨ 143/5TC

Y

⇨ 182/4TC

For Modular
Base Type B

K45R ⇨ ø5/8"

K50R ⇨ ø5/8"

K63R ⇨ ø7/8"

K85R ⇨ ø1"-1/8"

On request
IEC Flanges

B14**P=63**

(ø 90mm)
Stainless steel

Q=71

(ø 105mm)
Stainless steel

R=80

(ø 120mm)
Stainless steel

T=90

(ø 140mm)
Stainless steel

U=100

112
(ø 160mm)
Stainless steel

B3

↓
Mounting
Position