







STANDARD LUBRICATION & MOUNTING POSITIONS









UNITS K45A TO K85A ARE SUPPLIED WITH SYNTHETIC OIL, PROVIDING " LONG LIFE " LUBRICATION FOR THE MOUNTING POSITIONS B8 - B3 - B6 - B7 (FOR V5 - V6 SPECIFY IN THE ORDER).

* Standard Kel-Tech Oil Type

	TEMPERATURE			DIN 51517-3 ISO 12925-1
	-122 ^F	+32 ^F	+176 ^F	
 Telium VSF 320 *	-22 ^F		+176 ^F	synthetic
 Omala HD320	-13 ^F		+122 ^F	synthetic
 Spartan Synthetic EP 320	-13 ^F		+122 ^F	synthetic
 Klubersynth EG 4-320	-13 ^F		+122 ^F	synthetic

• Standard mounting positions

OIL QUANTITY FOR EVERY POSITION (OUNCES)

						
	B8	B3	B6	B7	V5	V6
K45A	2.82	2.82	2.82	2.82	▪	▪
K50A	4.58	4.58	4.58	4.58	▪	▪
K63A	10.6	10.6	10.6	10.6	▪	▪
K85A	42.33	42.33	42.33	42.33	▪	▪

Special Purpose Lubricants Available on request

▪ Please contact us for oil quantity