



ALL STAINLESS STEEL MOTORS

Three Phase 208-230/460 & 575V, NEMA Design B, High Efficiency, Squirrel Cage, TEFC, Class F Insulation, 40°C Ambient, Continuous Duty, 1.15 Service Factor.



- 300 Series Stainless Steel Construction
- CSA - C us CE Certified ULR
- Inverter duty - Nema MG 1 Part 31
- Washdown Duty Applications
- BISSC Certified
- Pharmaceutical & Food Processing
- Beverage Industry
- Mill and Chemical Duty
- Laser Etched Nameplate
- T-Drain included
- Oversized Bearings on both ends c/w Locked Drive-end
- Oversized Conduit Box c/w Lead Seal
- Drill & Tapped Drains
- Double Lip Contact Seals
- Corrosion Resistant

HP	RPM	Nema Frame	Model Number	
			208-230/460V	575V
1/4	1800	56C	SS1444C	SS1445C
1/3	1800	56C	SS1344C	SS1345C
1/2	1800	56C	SS1244C	SS1245C
3/4	1800	56C	SS3444C	SS3445C
1	1800	56C	SS0144C	SS0145C
1	1800	143TC	SS0144CT	SS0145CT
1.5	1800	56C	SS3244C	SS3245C
1.5	1800	145TC	SS3244CT	SS3245CT
2	1800	56C	SS0244C	SS0245C
2	1800	145TC	SS0244CT	SS0245CT
3	1800	182TC	SS0344CT	SS0345CT
5	1800	184TC	SS0544CT	SS0545CT
7.5	1800	213TC	SS7544CT	SS7545CT

* 1/4 - 3/4HP THESE RATINGS ARE ALSO AVAILABLE IN TENV (NON VENTILATED) FROM STOCK

ALL MODEL NUMBERS GIVEN ARE ROUND BODY MOTORS. FOR C-FLANGE MOTORS COMPLETE WITH BASE, ADD "F" AFTER THE MODEL NUMBER.



Double lip contact seals



Laser etched name plates



BISSC (Baking Industry Sanitation Standards Committee) Certified.



Completely Sealed Round Conduit box



Round Conduit Box Specifically Designed for the Food and Beverage Industry



Internally Locked Drive-End Bearing Construction